

CHECKWEIGHER CW 600/1200/3000/ 6000/10K (STANDARD SERIES)



- Modern Graphical User Interface
- Informative dashboard
- 3 level user ID
- Multi-weight classification
- 200 Products memory
- 7" Display
- Rejection confirmation (Optional)
- Data transfer to PC (Optional)
- Statistical data
- Printer interface



TECHNOFOUR ELECTRONICS PVT. LTD.

Leaders in Product Checking Systems

www.teplindia.com

All the Checkweigher Models ensure precise weight check of every product, the high accuracy and maximum throughput. Easy to use with intuitive colour touchscreen and icon-driven menus for fast product set up. The system is designed for easy removal for cleaning purpose.

SALIENT FEATURES

- Height Adjustment for Ease of Integration with Existing Lines
- Auto adjustment of conveyor speed according to throughput PPM
- Facility for Dynamic Weight Compensation
- Display of Net Weight
- Statistical Data of Total Accept, Total Reject, Standard Deviation
- Interlock with other machines
- Tendency control (optional)
- Various infeed mechanism like bottle separator, stabilizer, turn table etc. available

GENERAL SPECIFICATION

Model	weight Range (g)	Least count (g)	Accuracy (g)	Max speed (PPM)	Weighing conveyor size in mm (L X W)	Maximum product length allowed	Minimum product length allowed	Maximum product width allowed
CW 600 HSA	1-500	0.05	± 0.15	350	250 X 135	190	30	135
CW 600	1-500	0.05	± 0.2 to ± 0.4	120	250 X 135	190	30	135
CW 1200HSA	2-1000	0.10	± 0.15 to ± 0.29	250	350 X 180	280	35	180
CW 1200	2-1000	0.10	± 0.2 to ± 0.4	120	350 X 180	280	35	180
CW 3000HSA	04-2K	0.20	± 0.4 to ± 0.8	200	250 X 135	190	50	240
CW 3000	04-2K	0.20	± 1 to 1.2g	120	440 X 240	380	50	240
CW 6000	10-5K	0.50	± 2	100	500 X 280	420	50	280
CW 10K	20-10K	1.00	± 5	60	550 X 340	420	50	340

- **Power Requirement:** Single Phase 230V AC / 50Hz / 300VA
- **Rejection mechanism:** Air blow / Pusher / Diverter
- **Pneumatic Requirement:** 6Kgs / cm² for all rejection mechanisms



TECHNOFOUR ELECTRONICS PVT. LTD.

Kasurdi (Kheba), Khed Shivapur-Saswad Road,
Post: Khed Shivapur, Taluka: Bhore, District: Pune 412 205,
Maharashtra, India.
Tel: +91 7420070081 Email: marketing@tepl.co.in
Website: www.teplindia.com